

DP-51200 (51.2V 200AH)



Technical Specifications



Model Number	DP-51200
Nominal Voltage	51.2V
Rated Energy	10240wh
Nominal Capacity	200Ah
Cell Configuration	16S1P
Cycle Life	≥6000cyc@80%DOD@35°C
Monthly Self-Discharge Rate	3%/month
Charging Efficiency	≥97%
Discharge Efficiency	≥98%
Recommended Charging Voltage	57.6V
Recommended Charging Current	100A
Maximum Charging Voltage	58.4V
Maximum Charging Current	150A
Recommended Discharge Current	150A
Maximum Discharge Current	200A
Discharge Cut-off Voltage	43.2V
Battery Dimensions (W×D×H) (mm)	750.6*480.2*239.4MM
Packaging Dimensions (W×D×H) (mm)	795*555*395MM
Net Weight (kg)	85.8kg
Gross Weight (kg)	98.5kg
IP Rating	IP30
Enclosure Material	Case of metal
Charging Temperature Range	0°C~45C
Discharging Temperature Range	-20°C~60°C
Storage Temperature Range	0°C~40°C
Operating Humidity Range	10%-85%relative humidity (no condensation)
Communication Interface	CAN/RS232/RS485
Scalability	Max 15pieces in parallel

Product Features



Wide Applications Off-grid, HybridBack-up, Peak Shaving, and VirtualPower Plant Home Appliances,Uninterrupted Power Supply




Support a variety of communication protocols, support RS485,RS232.CAN



Long cycle life, using high-qualityLiFePO4 Cells, the cycle life is as highas 4500 times



Compatible with leading inverters



Intelligent battery managementsystem High reliability BMS, 10 year stested. Accurate & Stable



In the extreme performance safety test,the battery will not catch fire, explode,leak, and be safe to use.

Technical Specifications

